



Big Voice Processing for Small Business

Managing voice message processing is a key component of your telephone system. The Stratagy® IVP8 voice processing system integrates with the Strata® CIX™ business communication system to provide:

- > Automated Attendant to answer incoming calls
- > Call Routing to direct calls to the person or department the caller wants
- > Telephone Answering to take messages when an employee is unavailable
- > Voice Messaging to create, send, receive, forward, and save voice messages
- > Audiotext to play pre-recorded information on demand
- > Call Screening to announce the calling party
- > Message Notification to let users know when a voice message arrives
- > Unlimited Mailboxes to accommodate as many as your application requires

Stratagy voice processing gives you the ability to:

- > Simplify voice mailbox operation through an intuitive user interface

- > Record calls directly into your voice mailbox with a single button on your telephone
- > Communicate effectively both in and out of the office with other employees and customers 24 hours-a-day, 365 days-a-year

Customize voice processing functions using Stratagy's Token Programming, a powerful yet simple scripting language. Tokens can add or enhance voice mail features and functions such as recording and playback, audio files, or using DTMF entries by callers to provide data response or special call routing. Tokens can perform functions as simple as a hook-flash, and as complicated as an IVR application, specific to your needs. Token Programming is developed and deployed by Authorized Toshiba Dealers.

The Stratagy IVP8 integrates voice message processing on a single printed circuit card inside the Strata CIX chassis. Because there is no need for external connections, standard telephone ports, or separate power backup systems, the IVP8 decreases the cost and complexity of deploying voice mail applications.

SPECIFICATIONS

Strategy IVP8 Capacities	Minimum configuration 2 ports, expandable to 4, 6, or 8 ports via electronic upgrade. Message storage 15 hours, upgradeable to 30 hours. Unlimited mailboxes.			
Chassis Measurements	Width	Height	Depth	Weight
<i>Metric</i>	33 mm	191 mm	152 mm	.4 kg
<i>English</i>	1.3 in.	7.5 in.	6 in.	.8 lbs.
Power Supply Unit (PSU)	Uses hosting Strata CIX power supply			
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz).			
Power Backup	Provided by the power backup of the hosting Strata CIX chassis.			
Cooling	Convection			
Operating Temperature	39~104° F (4~40° C)			
Operating Humidity	20~80% relative humidity without condensation			
Storage Temperature	-4~140° F (-20~60° C)			
Chassis Installation	Printed circuit board installs in card slot in Strata CIX100, CIX200, or CIX670 chassis.			
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart J)			
Data Storage Media	Compact Flash 256MB, upgradeable to 512MB			
CPU	Embedded			
Memory	4MB			
Operating System	ROM DOS			
Voice Resources	On-board (8 channels maximum)			
Modem	Internal soft modem 14.4k baud			
Communication Ports	Two RS-232 COM ports			
Connection to Strata CIX	Direct backplane in slot in Strata CIX chassis			
Remote Access	Modem			
Standard Applications	Strategy Voice Mail, Auto Attendant, Token Programming.			
Optional Applications	IVR capabilities available via Token Programming or custom development.			
Application Installation	Deployed by Authorized Toshiba Dealers.			

Toshiba America Information Systems, Inc., Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697 www.telecom.toshiba.com

To locate an Authorized Dealer, call: (800) 222-5805

© 2008 Toshiba America Information Systems, Inc. All product, service and company names are trademarks, registered trademarks or service marks of their respective owners. Information including without limitation specifications, availability, content of services, and contact information is subject to change without notice.

Literature Order #: TSD-CIX-BR-IVP8-DS-VB/4500147

